

Digital handmätare för olja, med svivel i inloppet.
Elförsörjning med standardbatterier. Mätaren kan kalibreras för olika oljeviskositeter. Mätaren levereras med svart gummiskydd runt displayen.

Mätprincip:	Ovala kugghjul
Mätmängd:	0,005 l / puls
Flöde:	1-25 l / min
Max arbetstryck:	7 MPa / 1015 psi
Max arbetstemperatur:	60° C
Vätskans viskositet:	5-5000 mPa s (5,6-5600 cSt)
Noggrannhet:	± 1%
Display:	Flödesvolym: 4 siffror, 11,5 mm texthöjd. Total flödesvolym: 6 siffror, 5 mm texthöjd
Spänningskälla:	Batteri 2 x 1,5 V, storlek 1N
Batterilivslängd:	5000-20000 timmar
Anslutning inlopp:	Inv. ISO-G½
Anslutning utlopp:	Inv. ISO-G½
Vikt:	0,85 kg
Ingående material:	Aluminium, stål, polyester, nitrilgummi, plast
Art.nr:	**906365**

Digital hand meter for oil, with inlet swivel.
Powered by standard batteries. The meter can be calibrated for different oil viscosities. The display has a rubber protection cap.

Measuring principal:	*Oval gears*
Resolution:	*0.005 litre per pulse*
Flow range:	*1-25 litre per min*
Max working pressure:	*7 MPa (1015 psi)*
Max working temperature:	*60° C*
Viscosity range:	*5-5000 mPa s (5.6-5600 cSt)*
Accuracy:	*± 1%*
Display flow volume:	*4 digit 11.5 mm high*
Total flow volume:	*6 digits 5 mm high*
Power supply:	*2 x 1.5V alkaline batteries, size 1N*
Battery life:	*5000-20000 hrs*
Inlet connection:	*ISO-G½ female*
Outlet connection:	*ISO-G½ female*
Weight:	*0.85 kg*
Materials of construction:	*Aluminium, steel, polyurethane, nitrile rubber*
Part Number:	***906365***

Extra gummiskydd
till ovanstående mätare

Vikt:	0,05 kg
Art.nr:	**901244**

Extra rubber protection cap
for above meter

Weight:	*0.05 kg*
Part Number:	***901244***

Batteri
till ovanstående mätare
1,5 V, storlek 1N

Vikt:	0,01 kg
Art.nr:	**904591**

Battery
for above meter
1.5V size 1N

Weight:	*0.01 kg*
Part Number:	***904591***